

SUSTAINABLE, COST-CUTTING SILICONE SOLUTION

With the Silicone Roof Coating System from Mule-Hide Products, contractors can offer an environmentally friendly restoration option with:

Superior Resistance to Ponding Water—low water absorption outperforms conventional solvent and water-based protective roof coatings

Same Day Recoating—possible with its quick cure time

Low Odor—solvent-free formula; VOC compliant in all of North America

Energy Savings—meets CRRC® cool roof requirements by reflecting solar energy and reducing interior building temperatures. White 100% Silicone Roof Coating improves rooftop air conditioning unit efficiency.

Years of Durable, Low-maintenance Seamless Protection— control UV damage, reduce thermal shock, fully-adhered system seals off water entry points

Cost Savings—

Building Owner: No tear-off and disposal expense, minimal disruption

to building occupants

Contractor: Reduces labor with quick, easy application; nominal upfront equipment investment

Tax Relief—A tax advantage for building owners while saving energy! Expensing coatings versus capital depreciation lowers cash outlays and maximizes tax expense allowances.

Restore and repair the following roof types:

• EPDM

Asphalt

• TPO

Metal

PVC

- Concrete
- Modified Bitumen

material and system warranties. System warranties are available for commercial projects when installed in strict compliance with Mule-Hide's specifications by a Mule-Hide Warranty Eligible Contractor. Residential projects may qualify for material warranties. Complete warranty information and requirements for the various warranties available may be found on the Mule-Hide web site at

www.mulehide.com or by

contacting Mule-Hide at

800-786-1492.

WARRANTY PROGRAM

warranties for Commercial and

Residential projects including

Mule-Hide offers a variety of

"GREEN" ALTERNATIVE

Every year, roof tear-offs add millions of tons of roofing materials to landfills. Go green by choosing roof coatings to restore existing roofs. When it's time for the coatings to be renewed, additional product is added to the roof, continuing the sustainable mission to reduce landfill waste.



STEP-BY-STEP INSTALLATION

PREPARE

To ensure best results, prep substrate for priming:

• Si Cleaner

PRIME

Improve adhesion of the top coat by selecting the correct primer for the roofing substrate.

- Si 2-Part Epoxy Primer (BUR, modified bitumen, aluminum coated roofs or any area with ponding water)
- Si TPO Primer (TPO membrane)



Flexibility to use the thicker, mastic version of 100% Silicone Roof Coating as a multi-purpose sealant for repairs and maintenance along with reinforcement fabric.

- •100% Silicone Sealant
- \bullet TietexTM

COAT

Choose the right high-solids, 100% Silicone Coating with UV protection and reflectivity (white only):

- •100% Silicone Roof Coating (white, gray)
- •100% Silicone Masonry Wall Coating (white, gray)
- •100% Silicone Skylight Coating (clear)

CLEANUP

Wash tools & equipment.

•Si Cleaning Solvent



Prime



Seal





BEST PRACTICE TIP

Use 100% Silicone Roof Coating in Gray as a the first coat, or base coat, and use White as the second coat.

SILICONE ROOF COATING SYSTEM

Products Products										
	1 Gal	3.5 Gal	4 Gal	5 Gal	55 Gal	Shelf Life				
Si Cleaning Solvent	16MHSISOL1			16MHSISOL5		2 Years				
Si 2-Part Epoxy Primer Kit			16MHSIEPK1			1 Year				
100% Silicone Roof Coating	16MHSIRC1			16MHSIRC5	16MHSIRC55	1 Year				
100% Silicone Roof Coating Gray				16MHSIRC5G	16MHSIR55G	1 Year				
Si TPO Primer	16MHSITPR1			16MHSITPR5		2 Years				
100% Silicone Masonry Wall Coating	16MHSIMC1			16MHSIMC5	16MHSIMC55	1 Year				
100% Silicone Masonry Wall Coating Gray				16MHSIMC5G	16MHSIM55G	1 Year				
100% Silicone Roof Sealant	16MHSISEA1	16MHSISEA3				1 Year				
Si Cleaner				16MHSICL5	16MHSICL55	1 Year				
100% Silicone Skylight Coating	16MHSISC1			16MHSISC5		1 Year				

Accessories Accessories										
	4"x300'	6"x300'	12"x300'	20"x300'	40"x324'					
Tietex™ 325 Poly Fabric	09MHTT3043	09MHTT3063	09MHTT3123	09MHTT3203	09MHTT3403					
Tietex™ 272 Poly Fabric		09MHTT2063	09MHTT2123		09MHTT2403					

Refer to the Mule-Hide Product Data Sheets and Specifications for application information and coverage rates for each product. These documents may be obtained from the Mule-Hide website at www.mulehide.com or contact Mule-Hide at 800-786-1492.

"The name trusted in roofing since 1906"

Customer Line: 800-786-1492 • www.mulehide.com

Check our website monthly for the latest updates & technical bulletins.

National Support Center • 1195 Prince Hall Drive • Beloit, WI 53511 • tel. 608.365.3111 • fax. 608.365.7852



The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at www.mulehide.com prior to any installation for updated technical specifications and details. Mule-Hide is a U.S. registered trademark. All rights reserved.